


DRAGO Side Duo

LB6068.571-EN



IK08 IP66



[SLS]
Special linear, Side
throw - 145x45°



[SLS-FG]
Special linear, Side
throw - Frosted Glass
- 158x60°

Light distribution	[SLS] 145x45°, [SLS-FG] 158x60°
Luminaire luminous flux	614 - 1582 lm
Rated input power	10 - 20 W
CCT	2700K, 3000K, 4000K
CRI	Ra80
Control	On/Off, DALI
Product colours	
Height	25cm, 50cm, 80cm, 1m, Custom height (Please specify)
Luminaire efficacy	52 - 93 lm/W
Colour deviation	3 SDCM
BUG rating	B0-U0-G0
Lifetime L90B50 (hour)	>42, 000
Housing	Marine grade aluminum housing
Driver	Integral LED driver
Input voltage	220-240V 50/60Hz

Notes

3000K CCT or warmer must be selected to be DarkSky International certified., The photometry download contains two separate files, each representing one side of the lighting fixture. To accurately obtain the lighting characteristics for a double-headed layout, both files must be imported into the design software., For Wood-Look options, only the body part will be covered as the chosen texture. The head will be painted with HM2 standard colour.

Extras

Consult the factory	120-277V 50/60Hz
Luminaire body options	Double powder coating

Technical details

Certificates	CE, UKCA, DarkSky Approved
Mounting	Surface mountable
Finishing	Chromate conversion pretreatment followed by electrostatic powder coating
Fasteners	Stainless steel (AISI 304 / EN 1.4301 grade)
Gasket	Liquid silicone
Lens / Reflector	High reflectance aluminium coating, multifaceted micro reflector
Glass / Diffusor	Tempered safety glass
Impact protection	IK08
Ingress protection	IP66
Insulation class	Class I
Weight	4.11 kg (0.25 m), 5.67 kg (0.8 m)
LED module	High power LEDs on metal-core PCB
Driver surge protection	1/1 kV
Power factor	> 0.90
Through wiring	Single cable entry
Operating temperature	-40...50°C
Cable	0.2 m of flexible cable

HEPER HQ - HPR Pazarlama A.Ş.
Başkent OSB 22. Cd. No: 2,
Malıköy, Temelli, Sincan, 06909
Ankara, Turkey
+90 312 267 54 30
info@hepergroup.com

HEPER Europe GmbH
Ahornweg 5a, 58675
Hemer, Germany
+49 2372 568 7570
infoEU@hepergroup.com
www.heperlighting.com/de

We reserve the right to change specifications without prior written notice. Edition: 16.01.2026. For current version visit heperlighting.com. All flux (±7% tolerance) and power values (±10% tolerance) are derived following appropriate IES, CIE, and applicable standards.


Project name				Type		Quantity	
Date		Note					

LB6068.571-EN-__-__-__-__-EN-C1-__-__-__-__

Light distribution	Rated input power	Colour temperature	Control	Product colours
[SLS] Special linear, Side throw - 145x45° [SLS-FG] Special linear, Side throw - Frosted Glass - 158x60°	[350] 10 W [700] 20 W	[827] 2700 K CRI 80 [830] 3000 K CRI 80 [840] 4000 K CRI 80	[ONOFF] On/Off [DALI] DALI	[HM1]  Black [HM2]  Dark grey [HM3]  Anthracite grey [HM4]  Light grey [HM5]  White [HM6]  Bronze [CC]  Custom colour (Please specify RAL code)
Height	Extras	Accessories (<i>To be ordered separately</i>)		
[H00.25] 25cm [H00.50] 50cm [H00.80] 80cm [H01] 1m [HC] Custom height (Please specify)	Consult the factory	Anchorage		
	[UNI] 120-277V 50/60Hz	[628I000] 628I000		
	Luminaire body options			
	[DPC] Double powder coating			

Accessories (To be ordered separately)

Anchorage



628I000

628I000

Variant code	Light distribution	Luminaire luminous flux	Rated input power	CCT	CRI	Control	BUG rating
LB6068.571-EN-SLS-350-827	[SLS] Special linear, Side throw - 145x45°	854 lm	10 W	2700 K	Ra80	On/Off, DALI	B0-U0-G0
LB6068.571-EN-SLS-FG-350-827	[SLS-FG] Special linear, Side throw - Frosted Glass - 158x60°	614 lm	10 W	2700 K	Ra80	On/Off, DALI	
LB6068.571-EN-SLS-350-830	[SLS] Special linear, Side throw - 145x45°	886 lm	10 W	3000 K	Ra80	On/Off, DALI	B0-U0-G0
LB6068.571-EN-SLS-FG-350-830	[SLS-FG] Special linear, Side throw - Frosted Glass - 158x60°	636 lm	10 W	3000 K	Ra80	On/Off, DALI	
LB6068.571-EN-SLS-350-840	[SLS] Special linear, Side throw - 145x45°	930 lm	10 W	4000 K	Ra80	On/Off, DALI	B0-U0-G0
LB6068.571-EN-SLS-FG-350-840	[SLS-FG] Special linear, Side throw - Frosted Glass - 158x60°	670 lm	10 W	4000 K	Ra80	On/Off, DALI	
LB6068.571-EN-SLS-700-827	[SLS] Special linear, Side throw - 145x45°	1446 lm	20 W	2700 K	Ra80	On/Off, DALI	B0-U0-G0
LB6068.571-EN-SLS-FG-700-827	[SLS-FG] Special linear, Side throw - Frosted Glass - 158x60°	1034 lm	20 W	2700 K	Ra80	On/Off, DALI	
LB6068.571-EN-SLS-700-830	[SLS] Special linear, Side throw - 145x45°	1506 lm	20 W	3000 K	Ra80	On/Off, DALI	B0-U0-G0
LB6068.571-EN-SLS-FG-700-830	[SLS-FG] Special linear, Side throw - Frosted Glass - 158x60°	1074 lm	20 W	3000 K	Ra80	On/Off, DALI	
LB6068.571-EN-SLS-700-840	[SLS] Special linear, Side throw - 145x45°	1582 lm	20 W	4000 K	Ra80	On/Off, DALI	B0-U0-G0
LB6068.571-EN-SLS-FG-700-840	[SLS-FG] Special linear, Side throw - Frosted Glass - 158x60°	1132 lm	20 W	4000 K	Ra80	On/Off, DALI	