

HANDRA Side - Ø48 mm

LH5005.595-EN

CE UKCA IK10 IP65




22 mm
55/64"



39,3 mm
1 35/64"

40 mm
1 37/64"



56 mm
2 13/64"



[SLS]

Special linear, Side
throw - 44x52°

Light distribution
Luminaire luminous flux
Rated input power
CCT
CRI
Product colours
Luminaire efficacy
Colour deviation
BUG rating
Lifetime L90B50 (hour)
Housing
Driver
Input voltage

[SLS] 44x52°

38 - 40 lm

1 W

2700K, 3000K, 4000K

Ra80



38 - 40 lm/W

3 SDCM

B0-U0-G0

>102, 000

Marine grade aluminum housing

Remote LED driver (Multiple Products)

3VDC (Max) 350mA

Technical details

Certificates

CE, UKCA

Finishing

Chromate conversion pretreatment
followed by electrostatic powder coating

Fasteners

Stainless steel (AISI 304 / EN 1.4301 grade)

Gasket

Liquid gasket

Lens / Reflector

High reflectance aluminium coating

Glass / Diffusor

Custom Design PMMA Diffusor

Impact protection

IK10

Ingress protection

IP65

Insulation class

Class III

Weight

0.05 kg

LED module

High power LEDs on metal-core PCB

Through wiring

Single cable entry

Operating temperature

-25...50°C

Cable

0.2 m of flexible cable

Packing box dimensions

7*7*7 cm

HEPER HQ - HPR Pazarlama A.Ş.
Başkent OSB 22. Cd. No: 2,
Malıköy, Temelli, Sincan, 06909
Ankara, Turkey
+90 312 267 54 30
info@hepergroup.com

HEPER Europe GmbH
Ahornweg 5a, 58675
Hemer, Germany
+49 2372 568 7570
infoEU@hepergroup.com
www.heperlighting.com/de


We reserve the right to change specifications without prior written notice. Edition: 25.02.2026. For current version visit heperlighting.com. All flux ($\pm 7\%$ tolerance) and power values ($\pm 10\%$ tolerance) are derived following appropriate IES, CIE, and applicable standards.

Project name		Type		Quantity	
Date		Note			
LH5005.595-EN-____-____-____-____-CC-3V-350-C3-____					

Light distribution	Rated input power	Colour temperature	Control	Product colours
[SLS] Special linear, Side throw - 44x52°	[350] 1 W	[827] 2700 K CRI 80 [830] 3000 K CRI 80 [840] 4000 K CRI 80		[HM1]  Black [HM2]  Dark grey [HM3]  Anthracite grey [HM4]  Light grey [HM5]  White [HM6]  Bronze [CC]  Custom colour (Please specify RAL code)
Accessories (<i>To be ordered separately</i>)				
Mounting accessories				
[007502063] DALI & On/Off driver within an IP67 box for 1 to 6 HANDRA modules				
[007502064] DALI & On/Off driver within an IP67 box for 7 to 15 HANDRA modules				

Accessories (To be ordered separately)


Mounting accessories



**DALI & On/Off
driver within an
IP67 box for 1 to 6
HANDRA modules**

007502063

Mounting accessories



**DALI & On/Off
driver within an
IP67 box for 7 to
15 HANDRA
modules**

007502064

Variant code	Light distribution	Luminaire luminous flux	Rated input power	CCT	CRI	Control	BUG rating
LH5005.595-EN-SLS-350-827	[SLS] Special linear, Side throw - 44x52°	38 lm	1 W	2700K	Ra80		B0-U0-G0
LH5005.595-EN-SLS-350-830	[SLS] Special linear, Side throw - 44x52°	39 lm	1 W	3000K	Ra80		
LH5005.595-EN-SLS-350-840	[SLS] Special linear, Side throw - 44x52°	40 lm	1 W	4000K	Ra80		B0-U0-G0