

D-LIGHT V2 AFX 2 Module



LL2024.862-EN



IK08 IP66



UPCOMING



[P4]

Special pedestrian road distribution - right side traffic - 20x78°



[T1]

Type I, Asymmetric, Side throw - 111x48°



[T2]

Type II, Asymmetric, Side throw - 133x48°



[T2-2]

Type II, Asymmetric, Side throw - 149x54°



[T3]

Type III, Asymmetric, Side throw - 143x63°



[T4]

Type IV, Asymmetric, Forward throw - 117x64°



[T5]

Type V, Symmetric - 117°

Light distribution

[P4] 20x78°, [T1] 111x48°, [T2] 133x48°, [T2-2] 149x54°, [T3] 143x63°, [T4] 117x64°, [T5] 117°

Luminaire luminous flux

4045 - 9085 lm

Rated input power

34 - 67 W

CCT

3000K, 4000K

CRI

Ra70

Control

On/Off, DALI, AutoDIM, StepDIM

Product colours



Luminaire efficacy

114 - 144 lm/W

Colour deviation

3 SDCM, 4 SDCM

BUG rating

B1-U0-G1, B2-U0-G1, B3-U0-G1, B2-U0-G0

Lifetime L90B10 (hour)

>102, 000

Housing

Marine grade aluminum housing

Driver

Integral LED driver

Input voltage

220-240V 50/60Hz

Prismatic Glass enhances visual comfort and alters light distribution, reducing delivered lumens by approximately 10%. For specifications with Prismatic Glass and photometry files, please contact the factory.

Notes

Extras

Light output

Constant light output, Prismatic Glass

Consult the factory

Class II, 120-277V 50/60Hz

Technical details

Certificates

CE, UKCA, ENEC

Mounting

Direct pole or side bracket mountable. Spigot: Ø60 mm x 100 mm

Tilt angle

+15°/-15°

Finishing

Chromate conversion pretreatment followed by electrostatic powder coating

Fasteners

Stainless steel (AISI 304 / EN 1.4301 grade)

Gasket

EPDM gasket (Shore A 20-25)

Lens / Reflector

PMMA lens with high optical efficiency

Glass / Diffusor

Tempered safety glass

Impact protection

IK08

Ingress protection

IP66

Insulation class

Class I

Weight

7.3 kg

LED module

High power LEDs on metal-core PCB

Driver surge protection

10/6 kV

Power factor

< 0.95

Through wiring

Single cable entry

Operating temperature

-40...50°C

Cable

0.2 m of flexible cable

HEPER HQ - HPR Pazarlama A.Ş.
Başkent OSB 22. Cd. No: 2,
Malıköy, Temelli, Sincan, 06909
Ankara, Turkey
+90 312 267 54 30
info@hepergroup.com

HEPER Europe GmbH
Ahornweg 5a, 58675
Hemer, Germany
+49 2372 568 7570
infoEU@hepergroup.com
www.heperlighting.com/de

We reserve the right to change specifications without prior written notice. Edition: 31.10.2025. For current version visit heperlighting.com. All flux ($\pm 7\%$ tolerance) and power values ($\pm 10\%$ tolerance) are derived following appropriate IES, CIE, and applicable standards.

Project name				Type		Quantity	
Date		Note					

LL2024.862-EN-**-EN-C1-**

Light distribution	Rated input power	Colour temperature	Control	Product colours
[P4] Special pedestrian road distribution-right side traffic - 20x78° [T1] Type I, Asymmetric, Side throw - 111x48° [T2] Type II, Asymmetric, Side throw - 133x48° [T2-2] Type II, Asymmetric, Side throw - 149x54° [T3] Type III, Asymmetric, Side throw - 143x63° [T4] Type IV, Asymmetric, Forward throw - 117x64° [T5] Type V, Symmetric - 117°	[350] 34 W [500] 48 W [700] 67 W	[730] 3000 K CRI 70 [740] 4000 K CRI 70	[ONOFF] On/Off [DALI] DALI [AUTO] AutoDIM [STEP] StepDIM	[HM3]  Anthracite grey [HM4]  Light grey [CC]  Custom colour (Please specify RAL code)
Extras				
Light output				
[CLO] Constant light output [PG] Prismatic Glass				
Consult the factory				
[C2] Class II [UNI] 120-277V 50/60Hz				

Poles (To be ordered separately)

Cylindrical aluminum poles with flange plate

	Diameter / Dimensions	Height	Spigot diameter
	Ø114mm,	3m, 4m, 5m, 6m,	Ø114mm,
	Ø122mm,	7m, 8m, 9m	Ø122mm,
	Ø148mm, Ø165mm		Ø148mm, Ø165mm

Conical aluminum poles with embedded base

	Diameter / Dimensions	Height	Spigot diameter
	Ø114mm,	10m, 11m, 12m,	Ø60mm, Ø76mm,
	Ø122mm,	3m, 4m, 5m, 6m,	Ø90mm
	Ø148mm,	7m, 8m, 9m	
	Ø165mm,		
	Ø180mm, Ø200mm		

Conical aluminum poles with flange plate

	Diameter / Dimensions	Height	Spigot diameter
	Ø114mm,	10m, 11m, 12m,	Ø60mm, Ø76mm,
	Ø122mm,	3m, 4m, 5m, 6m,	Ø90mm
	Ø148mm,	7m, 8m, 9m	
	Ø165mm,		
	Ø180mm, Ø200mm		

Cylindrical aluminium poles with embedded base

	Diameter / Dimensions	Height	Spigot diameter
	Ø114mm,	3m, 4m, 5m, 6m,	Ø114mm,
	Ø122mm,	7m, 8m, 9m	Ø122mm,
	Ø148mm, Ø165mm		Ø148mm, Ø165mm

Variant code	Light distribution	Luminaire luminous flux	Rated input power	CCT	CRI	Control	BUG rating
LL2024.862-EN-T1-350-730	[T1] Type I, Asymmetric, Side throw - 111x48°	4530 lm	34 W	3000 K	Ra70	On/Off, DALI, AutoDIM, StepDIM	B2-U0-G1
LL2024.862-EN-T2-350-730	[T2] Type II, Asymmetric, Side throw - 133x48°	4230 lm	34 W	3000 K	Ra70	On/Off, DALI, AutoDIM, StepDIM	B1-U0-G1
LL2024.862-EN-T2-2-350-730	[T2-2] Type II, Asymmetric, Side throw - 149x54°	4300 lm	34 W	3000 K	Ra70	On/Off, DALI, AutoDIM, StepDIM	B1-U0-G1
LL2024.862-EN-T3-350-730	[T3] Type III, Asymmetric, Side throw - 143x63°	4045 lm	34 W	3000 K	Ra70	On/Off, DALI, AutoDIM, StepDIM	B1-U0-G1
LL2024.862-EN-T4-350-730	[T4] Type IV, Asymmetric, Forward throw - 117x64°	4240 lm	34 W	3000 K	Ra70	On/Off, DALI, AutoDIM, StepDIM	B1-U0-G1
LL2024.862-EN-T5-350-730	[T5] Type V, Symmetric - 117°	4400 lm	34 W	3000 K	Ra70	On/Off, DALI, AutoDIM, StepDIM	B2-U0-G0
LL2024.862-EN-P4-350-730	[P4] Special pedestrian road distribution-right side traffic - 20x78°	4400 lm	34 W	3000 K	Ra70	On/Off, DALI, AutoDIM, StepDIM	B1-U0-G1
LL2024.862-EN-T1-350-740	[T1] Type I, Asymmetric, Side throw - 111x48°	4830 lm	34 W	4000 K	Ra70	On/Off, DALI, AutoDIM, StepDIM	B2-U0-G1
LL2024.862-EN-T2-350-740	[T2] Type II, Asymmetric, Side throw - 133x48°	4510 lm	34 W	4000 K	Ra70	On/Off, DALI, AutoDIM, StepDIM	B1-U0-G1
LL2024.862-EN-T2-2-350-740	[T2-2] Type II, Asymmetric, Side throw - 149x54°	4585 lm	34 W	4000 K	Ra70	On/Off, DALI, AutoDIM, StepDIM	B1-U0-G1
LL2024.862-EN-T3-350-740	[T3] Type III, Asymmetric, Side throw - 143x63°	4315 lm	34 W	4000 K	Ra70	On/Off, DALI, AutoDIM, StepDIM	B1-U0-G1
LL2024.862-EN-T4-350-740	[T4] Type IV, Asymmetric, Forward throw - 117x64°	4520 lm	34 W	4000 K	Ra70	On/Off, DALI, AutoDIM, StepDIM	B1-U0-G1
LL2024.862-EN-T5-350-740	[T5] Type V, Symmetric - 117°	4690 lm	34 W	4000 K	Ra70	On/Off, DALI, AutoDIM, StepDIM	B2-U0-G0
LL2024.862-EN-P4-350-740	[P4] Special pedestrian road distribution-right side traffic - 20x78°	4690 lm	34 W	4000 K	Ra70	On/Off, DALI, AutoDIM, StepDIM	B1-U0-G1
LL2024.862-EN-T1-500-730	[T1] Type I, Asymmetric, Side throw - 111x48°	6415 lm	48 W	3000 K	Ra70	On/Off, DALI, AutoDIM, StepDIM	B3-U0-G1
LL2024.862-EN-T2-500-730	[T2] Type II, Asymmetric, Side throw - 133x48°	6270 lm	48 W	3000 K	Ra70	On/Off, DALI, AutoDIM, StepDIM	B1-U0-G1
LL2024.862-EN-T2-2-500-730	[T2-2] Type II, Asymmetric, Side throw - 149x54°	6500 lm	48 W	3000 K	Ra70	On/Off, DALI, AutoDIM, StepDIM	B1-U0-G1
LL2024.862-EN-T3-500-730	[T3] Type III, Asymmetric, Side throw - 143x63°	5970 lm	48 W	3000 K	Ra70	On/Off, DALI, AutoDIM, StepDIM	B2-U0-G1
LL2024.862-EN-T4-500-730	[T4] Type IV, Asymmetric, Forward throw - 117x64°	6210 lm	48 W	3000 K	Ra70	On/Off, DALI, AutoDIM, StepDIM	B1-U0-G1

LL2024.862-EN-T5-500-730	[T5] Type V, Symmetric - 117°	6540 lm	48 W	3000 K	Ra70	On/Off, DALI, AutoDIM, StepDIM	B2-U0-G0
LL2024.862-EN-P4-500-730	[P4] Special pedestrian road distribution-right side traffic - 20x78°	6455 lm	48 W	3000 K	Ra70	On/Off, DALI, AutoDIM, StepDIM	B2-U0-G1
LL2024.862-EN-T1-500-740	[T1] Type I, Asymmetric, Side throw - 111x48°	6785 lm	48 W	4000 K	Ra70	On/Off, DALI, AutoDIM, StepDIM	B3-U0-G1
LL2024.862-EN-T2-500-740	[T2] Type II, Asymmetric, Side throw - 133x48°	6880 lm	48 W	4000 K	Ra70	On/Off, DALI, AutoDIM, StepDIM	B1-U0-G1
LL2024.862-EN-T2-2-500-740	[T2-2] Type II, Asymmetric, Side throw - 149x54°	6635 lm	48 W	4000 K	Ra70	On/Off, DALI, AutoDIM, StepDIM	B1-U0-G1
LL2024.862-EN-T3-500-740	[T3] Type III, Asymmetric, Side throw - 143x63°	6315 lm	48 W	4000 K	Ra70	On/Off, DALI, AutoDIM, StepDIM	B2-U0-G1
LL2024.862-EN-T4-500-740	[T4] Type IV, Asymmetric, Forward throw - 117x64°	6565 lm	48 W	4000 K	Ra70	On/Off, DALI, AutoDIM, StepDIM	B1-U0-G1
LL2024.862-EN-T5-500-740	[T5] Type V, Symmetric - 117°	6920 lm	48 W	4000 K	Ra70	On/Off, DALI, AutoDIM, StepDIM	B2-U0-G0
LL2024.862-EN-P4-500-740	[P4] Special pedestrian road distribution-right side traffic - 20x78°	6830 lm	48 W	4000 K	Ra70	On/Off, DALI, AutoDIM, StepDIM	B2-U0-G1
LL2024.862-EN-T1-700-730	[T1] Type I, Asymmetric, Side throw - 111x48°	8270 lm	67 W	3000 K	Ra70	On/Off, DALI, AutoDIM, StepDIM	B3-U0-G1
LL2024.862-EN-T2-700-730	[T2] Type II, Asymmetric, Side throw - 133x48°	8385 lm	67 W	3000 K	Ra70	On/Off, DALI, AutoDIM, StepDIM	B1-U0-G1
LL2024.862-EN-T2-2-700-730	[T2-2] Type II, Asymmetric, Side throw - 149x54°	8090 lm	67 W	3000 K	Ra70	On/Off, DALI, AutoDIM, StepDIM	B1-U0-G1
LL2024.862-EN-T3-700-730	[T3] Type III, Asymmetric, Side throw - 143x63°	7700 lm	67 W	3000 K	Ra70	On/Off, DALI, AutoDIM, StepDIM	B2-U0-G1
LL2024.862-EN-T4-700-730	[T4] Type IV, Asymmetric, Forward throw - 117x64°	8005 lm	67 W	3000 K	Ra70	On/Off, DALI, AutoDIM, StepDIM	B2-U0-G1
LL2024.862-EN-T5-700-730	[T5] Type V, Symmetric - 117°	8435 lm	67 W	3000 K	Ra70	On/Off, DALI, AutoDIM, StepDIM	B3-U0-G1
LL2024.862-EN-P4-700-730	[P4] Special pedestrian road distribution-right side traffic - 20x78°	8325 lm	67 W	3000 K	Ra70	On/Off, DALI, AutoDIM, StepDIM	B2-U0-G1
LL2024.862-EN-T1-700-740	[T1] Type I, Asymmetric, Side throw - 111x48°	8925 lm	67 W	4000 K	Ra70	On/Off, DALI, AutoDIM, StepDIM	B3-U0-G1
LL2024.862-EN-T2-700-740	[T2] Type II, Asymmetric, Side throw - 133x48°	9085 lm	67 W	4000 K	Ra70	On/Off, DALI, AutoDIM, StepDIM	B1-U0-G1
LL2024.862-EN-T2-2-700-740	[T2-2] Type II, Asymmetric, Side throw - 149x54°	8675 lm	67 W	4000 K	Ra70	On/Off, DALI, AutoDIM, StepDIM	B1-U0-G1
LL2024.862-EN-T3-700-740	[T3] Type III, Asymmetric, Side throw - 143x63°	8240 lm	67 W	4000 K	Ra70	On/Off, DALI, AutoDIM, StepDIM	B2-U0-G1
LL2024.862-EN-T4-700-740	[T4] Type IV, Asymmetric, Forward throw - 117x64°	8705 lm	67 W	4000 K	Ra70	On/Off, DALI, AutoDIM, StepDIM	B2-U0-G1

LL2024.862-EN-T5-700-740	[T5] Type V, Symmetric - 117°	8940 lm	67 W	4000 K	Ra70	On/Off, DALI, AutoDIM, StepDIM	B3-U0-G1
LL2024.862-EN-P4-700-740	[P4] Special pedestrian road distribution-right side traffic - 20x78°	9025 lm	67 W	4000 K	Ra70	On/Off, DALI, AutoDIM, StepDIM	B2-U0-G1