


TURA 3x12 LED

LL2036.753-EN



IK08 IP66



Light distribution

[P4] 22x77°, [T1] 113x48°, [T2] 137x52°,
[T2-2] 150x60°, [T2BL] 128x48°, [T3]
143x68°, [T3-2] 158x59°, [T3BL] 128x50°,
[T4] 121x70°, [T4BL] 121x32°, [T4BL-2]
127x32°

Luminaire luminous flux

8064 - 11880 lm

Rated input power

80 W

CCT

3000K, 4000K

CRI

Ra70

Control

On/Off, DALI, AutoDIM, StepDIM

Product colours



Luminaire efficacy

100 - 149 lm/W

Colour deviation

3 SDCM, 4 SDCM

BUG rating

B3-U0-G3, B3-U0-G2, B3-U0-G1, B2-U0-G1,
B3-U1-G3, B3-U1-G2, B2-U1-G2

Lifetime L90B10 (hour)

>102, 000

Housing

Marine grade aluminum housing

Driver

Integral LED driver

Input voltage

220-240V 50/60Hz

Notes

This product can be supplied with
Insulation class (Class II) upon request.
Please contact factory.

Extras

External surge protection

10 kV

Connectivity

NEMA socket - 7 Pin

Light output

Constant light output

Consult the factory

Class II, 120-277V 50/60Hz

Luminaire body options

Double powder coating

Technical details

Certificates

CE, UKCA, ENEC

Mounting

Direct pole or side bracket mountable.
Spigot: Ø60 mm x 100 mm

Tilt angle

+15°/-15°

Finishing

Chromate conversion pretreatment
followed by electrostatic powder coating

Fasteners

Stainless steel (AISI 304 / EN 1.4301 grade)

Gasket

EPDM gasket (Shore A 20-25)

Lens / Reflector

PMMA lens with high optical efficiency

Glass / Diffusor

Tempered safety glass

Impact protection

IK08

Ingress protection

IP66

Insulation class

Class I

Wind catching area (EPA)

0.25 m²

Weight

10 kg

LED module

High power LEDs on metal-core PCB

Driver surge protection

8/6 kV

Power factor

> 0.95

Through wiring

Single cable entry

Operating temperature

-40...50°C

Cable

1 m of flexible cable



[P4]

Special pedestrian
road distribution-
right side traffic -
22x77°



[T1]

Type I, Asymmetric,
Side throw - 113x48°



[T2]

Type II, Asymmetric,
Side throw - 137x52°



[T2-2]

Type II, Asymmetric,
Side throw - 150x60°



[T2BL]

Type II, Asymmetric,
Side throw with
Backlight shield -
128x48°



[T3]

Type III, Asymmetric,
Side throw - 143x68°



[T3-2]

Type III, Asymmetric,
Side throw - 158x59°



[T3BL]

Type III, Asymmetric,
Side throw with
Backlight shield -
128x50°



[T4]

Type IV, Asymmetric,
Forward throw -
121x70°

HEPER HQ - HPR Pazarlama A.Ş.

Başkent OSB 22. Cd. No: 2,
Malıköy, Temelli, Sincan, 06909
Ankara, Turkey
+90 312 267 54 30
info@hepergroup.com

HEPER Europe GmbH

Ahornweg 5a, 58675
Hemer, Germany
+49 2372 568 7570
infoEU@hepergroup.com
www.heperlighting.com/de

We reserve the right to change specifications without prior
written notice. Edition: 17.06.2026. For current version visit
heperlighting.com. All flux (±%7 tolerance) and power values
(±%10 tolerance) are derived following appropriate IES, CIE,
and applicable standards.



[T4BL]

Type IV, Asymmetric,
Forward throw with
Backlight shield -
121x32°



[T4BL-2]

Type IV, Asymmetric,
Forward throw with
Backlight shield -
127x32°

Project name		Type		Quantity	
Date		Note			
LL2036.753-EN-__-__-__-__-EN-C1-__-__-__-__-__-__-__					

Light distribution	Rated input power	Colour temperature	Control	Product colours
[P4] ⁽¹⁾ Special pedestrian road distribution-right side traffic - 22x77° [T1] ⁽¹⁾ Type I, Asymmetric, Side throw - 113x48° [T2] ⁽¹⁾ Type II, Asymmetric, Side throw - 137x52° [T2-2] ⁽¹⁾ Type II, Asymmetric, Side throw - 150x60° [T2BL] ⁽¹⁾ Type II, Asymmetric, Side throw with Backlight shield - 128x48° [T3] ⁽¹⁾ Type III, Asymmetric, Side throw - 143x68° [T3-2] ⁽¹⁾ Type III, Asymmetric, Side throw - 158x59° [T3BL] ⁽¹⁾ Type III, Asymmetric, Side throw with Backlight shield - 128x50° [T4] ⁽¹⁾ Type IV, Asymmetric, Forward throw - 121x70° [T4BL] ⁽¹⁾ Type IV, Asymmetric, Forward throw with Backlight shield - 121x32° [T4BL-2] Type IV, Asymmetric, Forward throw with Backlight shield - 127x32°	[700] ⁽¹⁾ 80 W	[730] 3000 K CRI 70 [740] 4000 K CRI 70	[ONOFF] On/Off [DALI] DALI [AUTO] AutoDIM [STEP] StepDIM	[HM3]  Anthracite grey [HM4]  Light grey [CC]  Custom colour (Please specify RAL code)

Extras
External surge protection
[SP10] 10 kV
Connectivity
[NM7] NEMA socket - 7 Pin
Light output
[CLO] Constant light output
Consult the factory
[C2] Class II
[UNI] 120-277V 50/60Hz
Luminaire body options
[DPC] Double powder coating

Notes

(1) Light distribution [P4], [T1], [T2], [T2-2], [T2BL], [T3], [T3-2], [T3BL], [T4], [T4BL] is available with Rated input power [700]

Poles (To be ordered separately)

Cylindrical aluminum poles with flange plate

	Diameter / Dimensions	Height	Spigot diameter
	Ø114mm, Ø122mm, Ø148mm, Ø165mm	3m, 4m, 5m, 6m, 7m, 8m, 9m	Ø114mm, Ø122mm, Ø148mm, Ø165mm

Conical aluminum poles with embedded base

	Diameter / Dimensions	Height	Spigot diameter
	Ø114mm, Ø122mm, Ø148mm, Ø165mm, Ø180mm, Ø200mm	10m, 11m, 12m, 3m, 4m, 5m, 6m, 7m, 8m, 9m	Ø60mm, Ø76mm, Ø90mm

Conical aluminum poles with flange plate

	Diameter / Dimensions	Height	Spigot diameter
	Ø114mm, Ø122mm, Ø148mm, Ø165mm, Ø180mm, Ø200mm	10m, 11m, 12m, 3m, 4m, 5m, 6m, 7m, 8m, 9m	Ø60mm, Ø76mm, Ø90mm

Cylindrical aluminium poles with embedded base

	Diameter / Dimensions	Height	Spigot diameter
	Ø114mm, Ø122mm, Ø148mm, Ø165mm	3m, 4m, 5m, 6m, 7m, 8m, 9m	Ø114mm, Ø122mm, Ø148mm, Ø165mm

Variant code	Light distribution	Luminaire luminous flux	Rated input power	CCT	CRI	Control	BUG rating
LL2036.753-EN-T1-700-730	[T1] Type I, Asymmetric, Side throw - 113x48°	9066 lm	80 W	3000 K	Ra70	On/Off, DALI, AutoDIM, StepDIM	B3-U0-G1
LL2036.753-EN-T2-700-730	[T2] Type II, Asymmetric, Side throw - 137x52°	8548 lm	80 W	3000 K	Ra70	On/Off, DALI, AutoDIM, StepDIM	B3-U0-G2
LL2036.753-EN-T2-2-700-730	[T2-2] Type II, Asymmetric, Side throw - 150x60°	8744 lm	80 W	3000 K	Ra70	On/Off, DALI, AutoDIM, StepDIM	B3-U0-G3
LL2036.753-EN-T2BL-700-730	[T2BL] Type II, Asymmetric, Side throw with Backlight shield - 128x48°	8064 lm	80 W	3000 K	Ra70	On/Off, DALI, AutoDIM, StepDIM	B3-U1-G3
LL2036.753-EN-T3-700-730	[T3] Type III, Asymmetric, Side throw - 143x68°	8589 lm	80 W	3000 K	Ra70	On/Off, DALI, AutoDIM, StepDIM	B3-U0-G3
LL2036.753-EN-T3-2-700-730	[T3-2] Type III, Asymmetric, Side throw - 158x59°	9587 lm	80 W	3000 K	Ra70	On/Off, DALI, AutoDIM, StepDIM	B3-U1-G3
LL2036.753-EN-T3BL-700-730	[T3BL] Type III, Asymmetric, Side throw with Backlight shield - 128x50°	8099 lm	80 W	3000 K	Ra70	On/Off, DALI, AutoDIM, StepDIM	B3-U1-G3
LL2036.753-EN-T4-700-730	[T4] Type IV, Asymmetric, Forward throw - 121x70°	8525 lm	80 W	3000 K	Ra70	On/Off, DALI, AutoDIM, StepDIM	B3-U0-G3
LL2036.753-EN-T4BL-700-730	[T4BL] Type IV, Asymmetric, Forward throw with Backlight shield - 121x32°	8352 lm	80 W	3000 K	Ra70	On/Off, DALI, AutoDIM, StepDIM	B2-U1-G2
LL2036.753-EN-P4-700-730	[P4] Special pedestrian road distribution-right side traffic - 22x77°	8986 lm	80 W	3000 K	Ra70	On/Off, DALI, AutoDIM, StepDIM	B2-U0-G1
LL2036.753-EN-T1-700-740	[T1] Type I, Asymmetric, Side throw - 113x48°	11469 lm	80 W	4000 K	Ra70	On/Off, DALI, AutoDIM, StepDIM	B3-U0-G2
LL2036.753-EN-T2-700-740	[T2] Type II, Asymmetric, Side throw - 137x52°	11454 lm	80 W	4000 K	Ra70	On/Off, DALI, AutoDIM, StepDIM	B3-U0-G2
LL2036.753-EN-T2-2-700-740	[T2-2] Type II, Asymmetric, Side throw - 150x60°	11880 lm	80 W	4000 K	Ra70	On/Off, DALI, AutoDIM, StepDIM	B3-U0-G3
LL2036.753-EN-T2BL-700-740	[T2BL] Type II, Asymmetric, Side throw with Backlight shield - 128x48°	10908 lm	80 W	4000 K	Ra70	On/Off, DALI, AutoDIM, StepDIM	B3-U1-G3
LL2036.753-EN-T3-700-740	[T3] Type III, Asymmetric, Side throw - 143x68°	10953 lm	80 W	4000 K	Ra70	On/Off, DALI, AutoDIM, StepDIM	B3-U0-G3
LL2036.753-EN-T3-2-700-740	[T3-2] Type III, Asymmetric, Side throw - 158x59°	11439 lm	80 W	4000 K	Ra70	On/Off, DALI, AutoDIM, StepDIM	B3-U1-G3
LL2036.753-EN-T3BL-700-740	[T3BL] Type III, Asymmetric, Side throw with Backlight shield - 128x50°	10431 lm	80 W	4000 K	Ra70	On/Off, DALI, AutoDIM, StepDIM	B3-U1-G3
LL2036.753-EN-T4-700-740	[T4] Type IV, Asymmetric, Forward throw - 121x70°	11070 lm	80 W	4000 K	Ra70	On/Off, DALI, AutoDIM, StepDIM	B3-U0-G3
LL2036.753-EN-T4BL-700-740	[T4BL] Type IV, Asymmetric, Forward throw with Backlight shield - 127x32°	10542 lm	80 W	4000 K	Ra70	On/Off, DALI, AutoDIM, StepDIM	B3-U1-G2

LL2036.753-EN-P4-700-740	[P4] Special pedestrian road distribution-right side traffic - 22x77°	11577 lm	80 W	4000 K	Ra70	On/Off, DALI, AutoDIM, StepDIM	B2-U0-G1
--------------------------	---	----------	------	--------	------	--------------------------------	----------