



URBAN UNITS Adjustable Floodlight Module

LP4053.695-EN

CE UKCA IK08 IP65



Light distribution	[S] 7°, [N] 26°
Luminaire luminous flux	3355 - 4076 lm
Rated input power	35 W
CCT	2700K, 3000K, 4000K
CRI	Ra70, Ra80
Control	On/Off, DALI, AutoDIM, StepDIM
Product colours	
Height	3m, 4m, 5m
Luminaire efficacy	83 - 101 lm/W
Colour deviation	3 SDCM, 4 SDCM
BUG rating	B0-U5-G5
ULOR (%)	50.8 - 53.6
Lifetime L90B50 (hour)	>72, 600
Housing	Marine grade aluminum housing
Driver	Integral LED driver
Input voltage	220-240V 50/60Hz

Notes

Tilt angle adjustment of the module must be done in the factory environment and by the technical team. Please let your sales representative know about the angle degree information., Anchorage should be chosen according to the base pole height and not the total height.

Extras

Consult the factory	120-277V 50/60Hz
Luminaire body options	Double powder coating

Technical details

Certificates	CE, UKCA
Tilt angle	+30°/-30°
Finishing	Chromate conversion pretreatment followed by electrostatic powder coating
Fasteners	Stainless steel (AISI 304 / EN 1.4301 grade)
Gasket	Silicone
Lens / Reflector	High reflectance aluminium coating
Glass / Diffusor	UV stable, bio-based polycarbonate diffusor
Impact protection	IK08
Ingress protection	IP65
Insulation class	Class I
Weight	5.55 kg
LED module	Multi-chip high power LEDs on metal-core PCB
Driver surge protection	10/6 kV
Power factor	> 0.95
Through wiring	Single cable entry
Operating temperature	-40...50°C
Cable	0.2 m of flexible cable

HEPER HQ - HPR Pazarlama A.Ş.
Başkent OSB 22. Cd. No: 2,
Malıköy, Temelli, Sincan, 06909
Ankara, Turkey
+90 312 267 54 30
info@hepergroup.com

HEPER Europe GmbH
Ahornweg 5a, 58675
Hemer, Germany
+49 2372 568 7570
infoEU@hepergroup.com
www.heperlighting.com/de

We reserve the right to change specifications without prior written notice. Edition: 28.08.2025. For current version visit heperlighting.com. All flux (±7% tolerance) and power values (±10% tolerance) are derived following appropriate IES, CIE, and applicable standards.

Project name		Type		Quantity	
Date		Note			
LP4053.695-EN-__-__-__-__-EN-C1-__-__-__-__					

Light distribution	Rated input power	Colour temperature	Control	Product colours
[S] Spot - 7° [N] Narrow - 26°	[700] 35 W	[827] 2700 K CRI 80 [830] 3000 K CRI 80 [740] 4000 K CRI 70 [840] 4000 K CRI 80	[ONOFF] On/Off [DALI] DALI [AUTO] AutoDIM [STEP] StepDIM	[HM1] Black [HM2] Dark grey [HM3] Anthracite grey [HM4] Light grey [HM5] White [HM6] Bronze [CC] Custom colour (Please specify RAL code)
Height	Extras			
[H03] 3m	Consult the factory			
[H04] 4m	[UNI] 120-277V 50/60Hz			
[H05] 5m	Luminaire body options			
	[DPC] Double powder coating			

Poles (Included)

Product specific poles with flange plate



Product code	Height	Diameter / Dimensions	Spigot diameter
PAFC.URB-EN-H03	3m	Ø200mm	
PAFC.URB-EN-H04	4m	Ø200mm	
PAFC.URB-EN-H05	5m	Ø200mm	

Variant code	Light distribution	Luminaire luminous flux	Rated input power	CCT	CRI	Control	BUG rating
LP4053.695-EN-S-700-827	[S] Spot - 7°	3355 lm	35 W	2700 K	Ra80	On/Off, DALI, AutoDIM, StepDIM	
LP4053.695-EN-N-700-827	[N] Narrow - 26°	3355 lm	35 W	2700 K	Ra80	On/Off, DALI, AutoDIM, StepDIM	
LP4053.695-EN-S-700-830	[S] Spot - 7°	3397 lm	35 W	3000 K	Ra80	On/Off, DALI, AutoDIM, StepDIM	B0-U5-G5
LP4053.695-EN-N-700-830	[N] Narrow - 26°	3397 lm	35 W	3000 K	Ra80	On/Off, DALI, AutoDIM, StepDIM	B0-U5-G5
LP4053.695-EN-S-700-740	[S] Spot - 7°	4076 lm	35 W	4000 K	Ra70	On/Off, DALI, AutoDIM, StepDIM	B0-U5-G5
LP4053.695-EN-N-700-740	[N] Narrow - 26°	4076 lm	35 W	4000 K	Ra70	On/Off, DALI, AutoDIM, StepDIM	B0-U5-G5
LP4053.695-EN-S-700-840	[S] Spot - 7°	3810 lm	35 W	4000 K	Ra80	On/Off, DALI, AutoDIM, StepDIM	
LP4053.695-EN-N-700-840	[N] Narrow - 26°	3810 lm	35 W	4000 K	Ra80	On/Off, DALI, AutoDIM, StepDIM	