


URBAN UNITS V3 Top Module, 360°, 2 Module

LP4054.844-EN

CE UKCA IK08 IP65



[SYM]
Symmetric - 118°

Light distribution	[SYM] 118°
Luminaire luminous flux	4035 - 4490 lm
Rated input power	52 W
CCT	2700K, 3000K, 4000K
CRI	Ra80
Control	On/Off, DALI
Product colours	
Height	3m, 4m, 5m
Luminaire efficacy	77 - 86 lm/W
Colour deviation	3 SDCM
BUG rating	B2-U0-G1
Lifetime L90B50 (hour)	>60, 000
Housing	Marine grade aluminum housing
Driver	Integral LED driver
Input voltage	220-240V 50/60Hz
Notes	Anchorage should be chosen according to the base pole height and not the total height.

Extras

Consult the factory	120-277V 50/60Hz
Luminaire body options	Double powder coating

Technical details

Certificates	CE, UKCA
Finishing	Chromate conversion pretreatment followed by electrostatic powder coating
Fasteners	Stainless steel (AISI 304 / EN 1.4301 grade)
Gasket	Silicone
Lens / Reflector	High reflectance aluminium coating, multifaceted micro reflector
Glass / Diffusor	UV stable, bio-based polycarbonate diffusor
Impact protection	IK08
Ingress protection	IP65
Insulation class	Class I
Weight	12.83 kg
LED module	High power LEDs on metal-core PCB
Driver surge protection	6/6 kV
Power factor	> 0.95
Through wiring	Single cable entry
Operating temperature	-40...50°C
Cable	0.2 m of flexible cable

HEPER HQ - HPR Pazarlama A.Ş.
Başkent OSB 22. Cd. No: 2,
Malıköy, Temelli, Sincan, 06909
Ankara, Turkey
+90 312 267 54 30
info@hepergroup.com

HEPER Europe GmbH
Ahornweg 5a, 58675
Hemer, Germany
+49 2372 568 7570
infoEU@hepergroup.com
www.heperlighting.com/de

We reserve the right to change specifications without prior written notice. Edition: 28.08.2025. For current version visit heperlighting.com. All flux ($\pm 7\%$ tolerance) and power values ($\pm 10\%$ tolerance) are derived following appropriate IES, CIE, and applicable standards.

Project name				Type		Quantity	
Date		Note					
LP4054.844-EN-____-____-____-____-EN-C1-____-____-____-____							

Light distribution	Rated input power	Colour temperature	Control	Product colours
[SYM] Symmetric - 118°	[700] 52 W	[827] 2700 K CRI 80 [830] 3000 K CRI 80 [840] 4000 K CRI 80	[ONOFF] On/Off [DALI] DALI	[HM1]  Black [HM2]  Dark grey [HM3]  Anthracite grey [HM4]  Light grey [HM5]  White [HM6]  Bronze [CC]  Custom colour (Please specify RAL code)
Height	Extras			
[H03] 3m	Consult the factory			
[H04] 4m	[UNI] 120-277V 50/60Hz			
[H05] 5m	Luminaire body options			
	[DPC] Double powder coating			

Poles (Included)

Product specific poles with flange plate



Product code	Height	Diameter / Dimensions	Spigot diameter
PAFC.URB-EN-H03	3m	Ø200mm	
PAFC.URB-EN-H04	4m	Ø200mm	
PAFC.URB-EN-H05	5m	Ø200mm	

Variant code	Light distribution	Luminaire luminous flux	Rated input power	CCT	CRI	Control	BUG rating
LP4054.844-EN-SYM-700-827	[SYM] Symmetric - 118°	4035 lm	52 W	2700K	Ra80	On/Off, DALI	
LP4054.844-EN-SYM-700-830	[SYM] Symmetric - 118°	4420 lm	52 W	3000K	Ra80	On/Off, DALI	B2-U0-G1
LP4054.844-EN-SYM-700-840	[SYM] Symmetric - 118°	4490 lm	52 W	4000K	Ra80	On/Off, DALI	