



ZETA 8 Dyno

LR9012.583-EN



IK08 IP67



[WW]
Wall-wash - 45x85°

Light distribution	[WW] 45x85°
Luminaire luminous flux	1592 - 1766 lm
Rated input power	20 W
CCT	2700K, 3000K, 4000K
CRI	Ra80
Control	On/Off, DALI
Product colours	
Luminaire efficacy	76 - 88 lm/W
Colour deviation	3 SDCM
Lifetime L90B50 (hour)	>42, 000
Housing	Stainless steel housing (AISI 316L / EN 1.4404 grade)
Driver	Integral LED driver
Input voltage	220-240V 50/60Hz

Technical details

Certificates	CE, UKCA
Mounting	Ground recessed mountable
Fasteners	Stainless steel (AISI 304 / EN 1.4301 grade)
Gasket	Silicone
Lens / Reflector	High reflectance aluminium coating, multifaceted micro reflector
Glass / Diffusor	Tempered safety glass
Impact protection	IK08
Ingress protection	IP67
Insulation class	Class I
Weight	5.48 kg
LED module	High power LEDs on metal-core PCB
Driver surge protection	1/1 kV
Power factor	> 0.90
Through wiring	Single cable entry
Operating temperature	-40...50°C
Cable	0.3 m of rubber-sheathed cable

HEPER HQ - HPR Pazarlama A.Ş.
Başkent OSB 22. Cd. No: 2,
Malıköy, Temelli, Sincan, 06909
Ankara, Turkey
+90 312 267 54 30
info@hepergroup.com

HEPER Europe GmbH
Ahornweg 5a, 58675
Hemer, Germany
+49 2372 568 7570
infoEU@hepergroup.com
www.heperlighting.com/de


We reserve the right to change specifications without prior written notice. Edition: 03.03.2025. For current version visit heperlighting.com. All flux ($\pm 7\%$ tolerance) and power values ($\pm 10\%$ tolerance) are derived following appropriate IES, CIE, and applicable standards.

Project name		Type		Quantity	
Date		Note			
LR9012.583-EN-____-____-____-____-EN-C1-____					

Light distribution	Rated input power	Colour temperature	Control	Product colours
[WW] Wall-wash - 45x85°	[700] 20 W	[827] 2700 K CRI 80 [830] 3000 K CRI 80 [840] 4000 K CRI 80	[ONOFF] On/Off [DALI] DALI	[SS] Stainless steel 
Accessories (Included)	Accessories (To be ordered separately)			
Mounting accessories	Mounting accessories			
[007500618] Aluminium case for ZETA 8 Dyno / MOLTO 4 Hybrid	[160404012] Case removing vacuum [141407400] Connector set - 5-pole [141901135] Junction Box			

Accessories (Included)

Mounting accessories



**Aluminium case
for ZETA 8 Dyno /
MOLTO 4 Hybrid**

007500618

Accessories (To be ordered separately)


Mounting accessories



**Case removing
vacuum**

160404012


Mounting accessories



**Connector set - 5-
pole**

141407400

Mounting accessories



Junction Box

141901135

Variant code	Light distribution	Luminaire luminous flux	Rated input power	CCT	CRI	Control	BUG rating
LR9012.583-EN-WW-700-827	[WW] Wall-wash - 45x85°	1592 lm	20 W	2700K	Ra80		
LR9012.583-EN-WW-700-830	[WW] Wall-wash - 45x85°	1642 lm	20 W	3000K	Ra80		
LR9012.583-EN-WW-700-840	[WW] Wall-wash - 45x85°	1766 lm	20 W	4000K	Ra80		