


ZEROX S Dyno

LR9016.521-EN



IK10 IP67



[WW]
Wall-wash - 46x25°

Light distribution	[WW] 46x25°
Luminaire luminous flux	294 - 345 lm
Rated input power	4 W
CCT	2700K, 3000K, 4000K
CRI	Ra70, Ra80
Control	On/Off
Product colours	
Luminaire efficacy	73 - 86 lm/W
Colour deviation	3 SDCM, 4 SDCM
Lifetime L90B50 (hour)	>42, 000
Housing	Stainless steel housing (AISI 316L / EN 1.4404 grade)
Driver	Integral LED driver
Input voltage	220-240V 50/60Hz

Extras

Consult the factory	120-277V 50/60Hz
---------------------	------------------

Technical details

Certificates	CE, UKCA
Mounting	Ground recessed mountable
Fasteners	Stainless steel (AISI 304 / EN 1.4301 grade)
Gasket	Silicone
Lens / Reflector	High reflectance aluminium coating, multifaceted micro reflector
Glass / Diffusor	Tempered safety glass
Impact protection	IK10
Ingress protection	IP67
Insulation class	Class I
Weight	2.81 kg
LED module	High power LEDs on metal-core PCB
Driver surge protection	3/3 kV
Power factor	> 0.40
Through wiring	Single cable entry
Operating temperature	-40...50°C
Cable	0.3 m of rubber-sheathed cable

HEPER HQ - HPR Pazarlama A.Ş.
Başkent OSB 22. Cd. No: 2,
Malıköy, Temelli, Sincan, 06909
Ankara, Turkey
+90 312 267 54 30
info@hepergroup.com

HEPER Europe GmbH
Ahornweg 5a, 58675
Hemer, Germany
+49 2372 568 7570
infoEU@hepergroup.com
www.heperlighting.com/de

We reserve the right to change specifications without prior written notice. Edition: 23.09.2025. For current version visit heperlighting.com. All flux ($\pm 7\%$ tolerance) and power values ($\pm 10\%$ tolerance) are derived following appropriate IES, CIE, and applicable standards.

Project name		Type		Quantity	
Date		Note			
LR9016.521-EN-____-____-____-____-EN-C1-____-____					

Light distribution	Rated input power	Colour temperature	Control	Product colours
[WW] Wall-wash - 46x25°	[350] 4 W	[827] 2700 K CRI 80 [830] 3000 K CRI 80 [740] 4000 K CRI 70 [840] 4000 K CRI 80	[ONOFF] On/Off	[SS] Stainless steel 
Extras	Accessories (<i>To be ordered separately</i>)			
Consult the factory	Mounting accessories			
[UNI] 120-277V 50/60Hz	[160404012] Case removing vacuum [007502091] Plastic case for ZEROX S			


Accessories (To be ordered separately)

Mounting accessories Mounting accessories



Case removing vacuum

160404012



Plastic case for ZEROX S

007502091

Variant code	Light distribution	Luminaire luminous flux	Rated input power	CCT	CRI	Control	BUG rating
LR9016.521-EN-WW-350-827	[WW] Wall-wash - 46x25°	294 lm	4 W	2700K	Ra80	On/Off	
LR9016.521-EN-WW-350-830	[WW] Wall-wash - 46x25°	303 lm	4 W	3000K	Ra80	On/Off	
LR9016.521-EN-WW-350-740	[WW] Wall-wash - 46x25°	345 lm	4 W	4000K	Ra70	On/Off	
LR9016.521-EN-WW-350-840	[WW] Wall-wash - 46x25°	326 lm	4 W	4000K	Ra80	On/Off	