



NOX Linear

LT1031.750-EN

CE UKCA IK08 IP66



UPCOMING



[SYM]
Symmetric - 130°

Light distribution	[SYM] 130°
Luminaire luminous flux	4216 - 5164 lm
Rated input power	37 W
CCT	2700K, 3000K, 4000K, 5700K
CRI	Ra70, Ra80
Product colours	
Luminaire efficacy	114 - 140 lm/W
Colour deviation	3 SDCM, 4 SDCM, 5 SDCM
Housing	Stainless steel housing (AISI 316TI / EN 1.4571 grade)
Driver	Remote LED driver (Multiple Products)
Input voltage	45VDC (max) 700mA

Notes

This product can be supplied with Insulation class (Class II) upon request. Please contact factory. This product is compatible with 4-20 mA signal to further benefit advanced tunnel control systems such as data reading from luminance meters.

Extras

Light output	Constant light output
Consult the factory	120-277V 50/60Hz

Technical details

Certificates	CE, UKCA
Tilt angle	+30°/-30°
Finishing	Stainless steel housing (AISI 316TI / EN 1.4571 grade)
Fasteners	Stainless steel (AISI 316 / EN 1.4401 grade)
Gasket	Silicone
Glass / Diffusor	Tempered safety glass
Impact protection	IK08
Ingress protection	IP66
Insulation class	Class I
Weight	4.03 kg
LED module	High power LEDs on metal-core PCB
Through wiring	Single cable entry
Cable	1 m of halogen-free cable

HEPER HQ - HPR Pazarlama A.Ş.
Başkent OSB 22. Cd. No: 2,
Malıköy, Temelli, Sincan, 06909
Ankara, Turkey
+90 312 267 54 30
info@hepergroup.com

HEPER Europe GmbH
Ahornweg 5a, 58675
Hemer, Germany
+49 2372 568 7570
infoEU@hepergroup.com
www.heperlighting.com/de

We reserve the right to change specifications without prior written notice. Edition: 01.09.2026. For current version visit heperlighting.com. All flux ($\pm 7\%$ tolerance) and power values ($\pm 10\%$ tolerance) are derived following appropriate IES, CIE, and applicable standards.

Project name		Type		Quantity	
Date		Note			
LT1031.750-EN-____-____-____-CC-45-700-C1-____-____-____					

Light distribution	Rated input power	Colour temperature	Control	Product colours
[SYM] Symmetric - 130°	[700] 37 W	[827] 2700 K CRI 80 [730] 3000 K CRI 70 [830] 3000 K CRI 80 [740] 4000 K CRI 70 [840] 4000 K CRI 80 [757] 5700 K CRI 70		[SS] Stainless steel 
Extras	Accessories (<i>To be ordered separately</i>)			
Light output	Mounting accessories			
[CLO] Constant light output	[007502801] Control gear box for NOX LINEAR family			
Consult the factory				
[UNI] 120-277V 50/60Hz	[007502167] Preassembled cables and 3-pole connector set for NOX			

Accessories (To be ordered separately)


Mounting accessories



**Control gear box
for NOX LINEAR
family**

007502801

Mounting accessories



**Preamsembled
cables and 3-pole
connector set for
NOX**

007502167

Variant code	Light distribution	Luminaire luminous flux	Rated input power	CCT	CRI	Control	BUG rating
LT1031.750-EN-SYM-700-827	[SYM] Symmetric - 130°	4216 lm	37 W	2700K	Ra80		
LT1031.750-EN-SYM-700-730	[SYM] Symmetric - 130°	4776 lm	37 W	3000K	Ra70		
LT1031.750-EN-SYM-700-830	[SYM] Symmetric - 130°	4304 lm	37 W	3000K	Ra80		
LT1031.750-EN-SYM-700-740	[SYM] Symmetric - 130°	5128 lm	37 W	4000K	Ra70		
LT1031.750-EN-SYM-700-840	[SYM] Symmetric - 130°	4540 lm	37 W	4000K	Ra80		
LT1031.750-EN-SYM-700-757	[SYM] Symmetric - 130°	5164 lm	37 W	5700K	Ra70		