


HIP SKIRT SUS

SUSPENDED PROFILE

DARKON
THE EDGE OF LIGHT



TRIDONIC LED



ZHAGA



ASYMMETRIC



NARROW



DEGLARING




OPAL




INGRESS

IP22




92


STRAIGHT



FLARE




FIT




15

69



SURFACE MOUNTED


OR



RECESSED



Ø102MM



INTEGRAL DRIVER

DESIGN FEATURES

- Dot free homogeneous illumination
- Multiple snap fit lens options
- Up to 68 exit lumens per system watt
- High colour tolerance - MacAdam 3
- Complies with AS/NZS 60598.2.1
- Australian made
- Snap fit gear tray with integrated driver
- Spring loaded control joints
- 10 year extended warranty optional
- Miter joints available
- Multiple fixed output options
- Zhaga compliant
- 90+ colour rendering, 80+ available upon request
- L80 / F10 = 72,000 hours @ 450mA / 75°C TA
- Detailed shop drawings
- Supplied 100% pre-built
- Plug and play wire looms
- 5 year warranty
- Project specific labelling referencing type numbers
- Welded mitre joints eliminate light bleed

LUMEN PERFORMANCE

TRIDONIC FIXED WHITE / EXIT LUMENS

HE CRI80	200mA	626 lm p/mtr	10 W p/mtr
HE CRI80	250mA	772 lm p/mtr	12 W p/mtr
HE CRI80	300mA	928 lm p/mtr	14 W p/mtr
HE CRI80	350mA	1065 lm p/mtr	16 W p/mtr
HE CRI80	400mA	1218 lm p/mtr	18 W p/mtr
HE CRI80	450mA	1357 lm p/mtr	21 W p/mtr
HE CRI80	500mA	1486 lm p/mtr	23 W p/mtr
HE CRI80	200mA	626 lm p/mtr	10 W p/mtr
HE CRI80	250mA	772 lm p/mtr	12 W p/mtr
HE CRI80	300mA	928 lm p/mtr	14 W p/mtr
HE CRI80	350mA	1065 lm p/mtr	16 W p/mtr

Tested with white finish / 4K / Opal V lens

OPTIONS

SKIRT TYPE: Straight / Flare / Fit

FINISH: Black / White / Silver / Gold / Custom

SKIRT FINISH: Black / White / Silver / Gold / Custom

CEILING PLATE FINISH: White / Black

CEILING PLATE TYPE: Surface mounted / Recessed

SUSPENSION TYPE: 2m wire / 4m wire

LENS: Opal V / Deglaring / Asymmetric / Narrow

LED: HE / HO / Tunable white

CURRENT: 200 / 250 / 300 / 350 / 400 / 450 / 500 / 550 / 600mA

TEMP: 2700K / 3000K / 4000K / (2700K-6500K)

DIMMING: Non dim / DALI dim / SwitchDIM / DSI dim / Casambi

PROJECT:

REV: 29/07/2026

TYPE NO:

QTY:

DARKON.COM.AU