



DESIGN FEATURES

- Dot free homogeneous illumination with opal lens option
- Wide array of beam angles with clear lens option
- Track compatibility with Global / Stucchi / Eutrac / Powergear / Staff
- DIP switch selectable between multiple fixed output options
- DIP switch selectable between multiple colour temperatures
- Up to 180 exit lumens per watt
- 80+ or 90+ colour rendering
- UGR <19(30°&60°), <22(90°)
- High colour tolerance Macadam 3
- L90 100,000hrs / L80 50,000hrs / 25° Ta
- Complies with AS/NZS 60598.2.1
- Supplied 100% pre-built
- 5 year warranty
- 10 year extended warranty optional
- Project specific labelling referencing type numbers

LUMEN PERFORMANCE

SAMSUNG SMD2835

567:	10/12/15/17/20 W	1800-3600 lm
1129:	20/25/30/35/40 W	3600-7200 lm
1410:	24/30/36/42/48 W	4320-8640 lm

SYSTEM WATTAGE / EXIT LUMENS 4000K

OPTIONS

SIZE:	567 / 1129 / 1410
COLOUR:	White / Black
LENS:	Opal* / Clear
COLOUR TEMP:	3000K / 4000K / 5000K [DIP Selectable]
OPTIC:	30x30° / 60x60° / 60x90° / 90x90° / 120° / Double Symmetri 25° / Asymmetric 25° / Asymmetric 35°
DIMMING:	Non Dim [DIP Selectable Power 1 - 5]

*120° only