



SLIM TRADIE SUS

SUSPENDED PROFILE

DARKON
THE EDGE OF LIGHT



DESIGN FEATURES

- Dot free homogeneous illumination
- Multiple snap fit lens options
- Up to 98 exit lumens per system watt
- High colour tolerance - MacAdam 3
- Complies with AS/NZS 60598.2.1
- Detailed shop drawings
- Supplied 100% pre-built
- Plug and play wire looms
- 5 year warranty
- Project specific labelling referencing type numbers
- Welded mitre joints eliminate light bleed
- Sliding 'sus saddle' detail for adjustable suspension spacing
- Low glare UGR≤19
- Multiple fixed output options
- Zhaga compliant
- 90+ colour rendering, 80+ available upon request
- L80 / F10 = 72,000 hours @ 450mA / 75°C TA
- Lap join milling - No Light Bleed
- Australian made
- Snap fit gear tray with integrated driver
- Spring loaded control joints
- 10 year extended warranty optional
- Miter joints available
- Factory fitted "push to join" installation
- Recessed lens to help reduce glare

LUMEN PERFORMANCE

TRIDONIC FIXED WHITE / EXIT LUMENS

HE CRI90	200mA	828 lm p/mtr	10 W p/mtr
HE CRI90	250mA	1028 lm p/mtr	12 W p/mtr
HE CRI90	300mA	1225 lm p/mtr	14 W p/mtr
HE CRI90	350mA	1414 lm p/mtr	16 W p/mtr
HE CRI90	400mA	1601 lm p/mtr	18 W p/mtr
HE CRI90	450mA	1785 lm p/mtr	21 W p/mtr
HE CRI90	500mA	1968 lm p/mtr	23 W p/mtr
HO CRI90	200mA	1652 lm p/mtr	17 W p/mtr
HO CRI90	250mA	2039 lm p/mtr	21 W p/mtr
HO CRI90	300mA	2415 lm p/mtr	26 W p/mtr
HO CRI90	350mA	2780 lm p/mtr	30 W p/mtr

Tested with white finish / 4K / Opal V lens

OPTIONS

FINISH: Black / White / Silver / Gold / Custom

CEILING PLATE FINISH: White / Black

CEILING PLATE TYPE: Surface mounted / Recessed

SUSPENSION TYPE: 2m wire / 4m wire

LENS: Opal V / Deglaring / Asymmetric / Narrow

LED: HE / HO / Tunable white

CURRENT: 200 / 250 / 300 / 350 / 400 / 450 / 500 / 550 / 600mA

TEMP: 2700K / 3000K / 4000K / (2700K-6500K)

DIMMING: Non dim / DALI dim / SwitchDIM / DSI dim / Casambi

PROJECT:

REV: 11/08/2026

TYPE NO:

QTY:

DARKON.COM.AU